

Wall Textiles

Specifications

WEAVE	SIZE	WEIGHT (+/- 10%) OZ/Y ²	WEIGHT (+/- 10%) KG/M ²	THICKNESS (+/- 10%) INCHES	THICKNESS (+/- 10%) MM
Bamboo	72" (1.83 m)	20.06	0.584	0.059	1.50
Basketweave, FG-Core	72" (1.83 m)	30.70	0.870	0.072	1.83
Basketweave, P-Core	72" (1.83 m)	25.80	0.731	0.070	1.78
Bouclé	72" (1.83 m)	25.80	0.731	0.071	1.80
Dart	72" (1.83 m)	30.70	0.870	0.072	1.83
Frost	72" (1.83 m)	38.40	1.089	0.104	2.64
Glow	70" (1.78 m)	18.70	0.530	0.056	1.42
Ikat	72" (1.83 m)	27.70	0.785	0.064	1.63
Mini Basketweave	72" (1.83 m)	22.20	0.629	0.060	1.52
Mosaic	72" (1.83 m)	22.20	0.629	0.063	1.60
Plaid	72" (1.83 m)	22.20	0.629	0.061	1.55
Reed	72" (1.83 m)	24.80	0.703	0.059	1.50
Rib Weave	72" (1.83 m)	33.50	0.950	0.090	2.29
Savile	72" (1.83 m)	25.80	0.731	0.071	1.80
Scout	72" (1.83 m)	22.20	0.629	0.068	1.73
Shade	72" (1.83 m)	26.90	0.763	0.066	1.68
Speckle	72" (1.83 m)	28.10	0.796	0.065	1.65
Tidal	72" (1.83 m)	23.20	0.656	0.101	2.57
Twill	72" (1.83 m)	24.20	0.686	0.063	1.60
Wabi Sabi	72" (1.83 m)	31.30	0.882	0.098	2.49
Wave	72" (1.83 m)	22.20	0.629	0.060	1.52

FLAMMABILITY ASTM E84 ADHERED

Class A
Class A

FLAMMABILITY ASTM E84 ADHERED

Class A
Class A

WALL TEXTILES DURABILITY ASTM F 793

Cat VI, Type III
Glow, Bamboo; Cat V, Type II

CLASSIFICATION

Commercial
Commercial

WINDOW COVERING NFPA 701 METHOD 1

Pass

ABRASION WYZENBEEK

100,000