

MAINTENANCE INSTRUCTIONS For Chilewich Wall Textile Products

Chilewich Wall Textile Products will deliver years of satisfactory service when maintained properly.

1. MAINTENANCE INSTRUCTIONS GENERAL

- 1.1 Chilewich Wall Textiles are made with a woven vinyl fabric bonded to nylon scrim backing. Vinyl is a very tough durable material and few household or common office chemicals affect it.
- 1.2 Routine maintenance along with periodic cleanings and diligent attention to stain-causing soils will provide a long useful life. The frequency of routine maintenance depends on the amount of soil and dirt to which the fabric is exposed.
- 1.3 Do not use Acetone, Pine-Sol or citrus-based cleaners as they can damage the Chilewich Wall Textile Products.
- 1.4 Dirt and smudges can be removed with mild soap (use the lowest-Ph detergent that proves to be successful) and warm water. A small area should be tested with all cleaners prior to use to ensure compatibility.
- 1.5 Cleaning from the bottom upward is most effective. Rinse thoroughly with clean water from the top down, using a sponge.
- 1.6 Dry Chilewich Wall Textiles with a lint-free towel or soft cloth.
- 1.7 Direct contact between natural rubber and Chilewich Wall Textiles will cause discoloration of the textile. Avoid use of natural rubber products with Chilewich Wall Textiles.

Please note: Stains that cannot be removed under the listed procedures can be treated with a 1:10 bleach to water solution. Mist the solution on the area of discoloration and allow to dwell for 5-10 minutes. Rinse the area with water only in order to remove the bleach residue. Allow to dry completely. Some stains may require professional service to complete the stain removal process.